

Lug & Ring Terminal Insulators

A more comprehensive line of insulators, offering a wider variety of lug and ring protection. Our lug and ring insulators can be used with starters, generators, alternators, solenoids, and other devices.



View inside the back cover for the Prop 65 Warning.



258 Series



- Protect large terminal connections from shorts
- Terminal Outside Dia: 2.3" / 58.7mm
- Post Height: 2.0" / 50.8mm
- Inside Grip Diameter: .65" / 16.6mm
- Can accept multiple cables, up to 1/0 ga each

Part #	Cable Entry Size
258N4	Round, 3/0 - 4/0
258N9	Oval, up to 4/0



216T Series



- Snap-on insulator, can be removed without cable
- Terminal Outside Dia: .64" / 16.3mm
- Post Height: .74" / 18.8mm

Part #	Cable Entry Size
216T8	.27" / 6.9mm



400 Series



- Terminal Outside Dia: .6" / 15.2mm
- Post Height: .88" / 22.4mm
- Inside Grip Dia: .44" / 11.2mm
- Terminal Length: 1.19" / 30.3mm

Part #	Cable Entry Size
400N7	.31" / 7.9mm
400N9	.44" / 11.2mm
400E4	.18" / 4.6mm



405 Series



- Terminal Outside Dia: 1.0" / 25.4mm
- Post Height: .98" / 24.8mm
- Inside Grip Diameter: .50" / 12.7mm

Part #	Cable Entry Size
405N1	.13" / 3.3 mm
405N2	.30" / 7.6mm
405N9	.50" / 12.7mm



406 Series

406N3	.16" / 4.1mm
406N9	.75" / 19mm



470 Series



- Terminal Outside Dia: .85" / 21.6mm
- Post Height: 1.06" / 26.9mm
- Inside Grip Diameter: .63" / 15.9mm
- Terminal Length: 1.81" / 46.0mm

Part #	Cable Entry Size
470N9	.63" / 15.9mm



485 Series



- Terminal Outside Dia: .52" / 12.9mm
- Post Height: .45" / 11.4mm
- Inside Grip Diameter: .25" / 6.4mm
- Cable Entry: .25" / 6.4mm

Part #	Cable Entry Size
485N9	.25" / 6.4mm



487 Series



- Terminal Outside Dia: 1.26" / 32mm
- Post Height: .98" / 24.9mm
- Inside Grip Dia: 1.0" / 25.4mm
- Available in 5 cable entries

Part #	Cable Entry Size
487N6	.5" / 12.7mm
487N7	.6" / 15.2mm
487N8	.65" / 16.5mm
487N9	.75" / 19mm
488N9	.87" / 22.1mm



488 Series

Lug & Ring Terminal Insulators

Continuation of our lug & ring terminal insulators



View inside the back cover for the Prop 65 Warning.

Terminal Insulators

Terminal Busbars

Power Posts

Power Bushings

Fuses & Fuse Holders



490 Series



- Used for angled connections
- Terminal Outside Dia: .75" / 19.1mm
- Post Height: 1.07" / 27.2mm
- Inside Grip Dia: .50" / 12.7mm

Part #	Cable Entry Size
490N9	.5" / 12.7mm



510 Series



- Terminal Outside Dia: .5" / 12.7mm
- Post Height: .8" / 20.3mm
- Inside Grip Diameter: 6.4 - 11.6mm
- Additional lead times may apply

Part #	Cable Entry Size
510N9	.25" / 6.4mm



600 Series



- Terminal Outside Dia: 1.57" / 40mm
- Post Height: 1.62" / 41.1mm
- Inside Grip Dia: .65" / 16.6mm
- Available in 7 cable entries

Part #	Cable Entry Size
600N1	(1) .31" / 7.9mm
600N2	(2) .31" / 7.9mm
600N3	(1) .5" / 12.7mm
600N4	(2) .5" / 12.7mm
600N5	(1) .62" / 15.8mm
600N6	(2) .62" / 15.8mm
600N7	Oval up to 4/0 ga



690 Series



- Protect medium duty right angle terminals
- Accept 8ga - 4/0ga cables

Part #	Cable Entry	Terminal Footprint
691N9	.16" / 3.9mm	.78 x 1.13" / 19.7 x 28.7mm
692N9	.24" / 6.2mm	.77 x 1.08" / 19.6 x 27.4mm
693N9	.27" / 6.9mm	.82 x 1.14" / 20.8 x 28.8mm
694N9	.29" / 7.4mm	.84 x 1.19" / 21.3 x 30.2mm
695N9	.32" / 8.2mm	.92 x 1.26" / 23.4 x 32mm
696N9	.35" / 8.9mm	1.02 x 1.22" / 25.9 x 31mm



800 Series



- Terminal Outside Dia: .73" / 18.5mm
- Post Height: 1.03" / 26.2mm
- Inside Grip Dia: .42" / 10.7mm
- Additional lead times may apply

Part #	Cable Entry Size
800N4	.17" / 4.3mm
800N5	.21" / 5.3mm
800N8	.31" / 7.9mm
800N9	.50" / 12.7mm



801 Series



- Terminal Outside Dia: .75" / 19.1mm
- Post Height: 1.03" / 26.2mm
- Inside Grip Dia: .37" / 9.4mm
- Cable Entry: .31" / 7.9mm

Part #	Cable Entry Size
801N8	.31" / 7.9mm



960 Series



- Protect heavy duty right angle terminals
- Accept 8ga - 4/0ga cables

Part #	Cable Entry	Terminal Footprint
962N9	.21" / 5.3mm	.77 x 1.18" / 19.4 x 30.0mm
963N9	.24" / 6.0mm	.75 x 1.35" / 19.1 x 34.2mm
964N9	.33" / 8.5mm	.81 x 1.36" / 20.6 x 34.6mm
965N9	.36" / 9.2mm	.90 x 1.49" / 22.9 x 37.8mm
966N9	.35" / 9.0mm	.97 x 1.50" / 24.5 x 38.2mm
967N9	.44" / 11.1mm	1.08 x 1.51" / 27.5 x 38.2mm
968N9	.44" / 11.1mm	1.16 x 1.60" / 29.5 x 40.5mm